2015 Aalborg Symposium on Microgrids

Survey of Microgrid R&D in Latin America

Guillermo Jiménez Estévez Rodrigo Palma-Behnke Patricio Mendoza Araya Felipe Valencia Ignacio Polanco





Contents

- 1. Microgrids opportunities and potential
- 2. Lessons learned from microgrid implementation
- 3. Microgrids development and status





Remote locations are the main microgrid development opportunity

Remote (off-grid) microgrids are best hope for developing world, according to the United Nations

Solution for climate change and ending energy poverty

Physical islands most attractive remote opportunity today

- High fuel costs and supply vulnerability
- Single negotiating party entity for larger scale systems






Remote locations are the main microgrid development opportunity

Technology Drivers

- Declining cost of solar PV
- High cost of diesel
- Three primary segments
 - Commodity extraction systems
 - Physical islands
 - Village electrification










Chile: Number of feasible isolated MG opportunities















Brazil: Isolated systems







Colombia: Isolated systems





Joint Research Groups









Contents

- 1. Microgrids opportunities and potential
- 2. Lessons learned from microgrids implementation
- 3. Microgrids development and status





- A collection of coordination control issues in microgrids should be elaborated in order to avoid falling in the same problems (i.e transitions diesel / inverter, low/high SoC at battery bank).
 - Incorporation of existing diesel engines requires determining parameters, so transitions between GenSet and BESS can be conducted in a proper way.
 - Establish clear maintenance procedures → risk of missing control adjustments.

 Electricity is not a unique energy source → explore the potential of RE to provide heat in more efficient ways.

- In the Latin American case, **funding** is mostly lead by private companies (**Social responsibility**). Academic institutions assume the role of developers. Promote strategic alliances among different actors. Local actors are key in terms of maintenance.
- Microgrid funding is associated to CAPEX, supporters are not interested on assuming OPEX → Develop business models that may ensure that OPEX can be covered in time.
- Even though **Energy Efficiency** can be promoted at community level, significative energy demand rise should be considered as a design and planning criterion.
- Definition with the community of a local **management structure** to ensure correct operation and maintenance practices.


 Microgrid developers are not "community planners"! Main contribution should be focused in the generation of opportunities for a local development (life quality, migration, productive projects).

 Co-construction schemes and a microgrid development methodology play a KEY role in the whole implementation process. If community is not incorporated from the beginning the project expected contribution present a high failure risk (Easter Island).

Contents

- 1. Microgrids opportunities and potential
- 2. Lessons learned from microgrids implementation
- 3. Microgrids development and status

smart integration \rightarrow innovation oportunities




smart integration \rightarrow innovation oportunities












Education, training

"Science questions comming from the community"

Control Issues EMS set points → Droop control








CENTRO DE ENERGÍA



Control Issues Operation mode examples











I. Transition BEES master mode to Diesel generator + BESS slave









I. Transition BEES master mode to Diesel generator + BESS slave




CENTRO DE ENERGÍA













I. Transition BEES master mode to Diesel generator + BESS slave






CENTRO DE ENERGÍA

II. External mantainance → change in parameters






II. External mantainance → change in parameter






II. External mantainance → change in parameter





II. External mantainance → change in parameter





III. Additional observed control issues

- Accuracy of UC to avoid coordination between set-points and feasible operation domain.
- System recovery after intentional/un-intentional black-outs → topology control strategy (switching).
- The use of non-linear loads such welding machines caused sudden disconnections of the solar panels.
- Battery equalization procedure is are neither automated in the SCADA nor included in the UC model.





Final comments

- Based on a six year long experience in a rural isolated microgrid project, several control issues are presented and analyzed.
- New challenges were identified for both, a more detailed UC/ EMS model able to avoid complex operational conditions and a framework for the analysis and design of control strategies and dynamic behavior.
- Test cases collection and structured description procedures can help to improve the penetration and effectiveness of this type of initiatives.
- Even though Huatacondo project is a specific pilot project, it is completely applicable to other Latin countries that face common challenges and characteristics like the Chilean ones.





2015 Aalborg Symposium on Microgrids

Survey of Microgrid R&D in Latin America



